

IR VARI-FOCAL DOME CAMERA

DI-330IPSVF



1/3" CMOS Sensor
 3 Mega-Pixel
 True Day & Night (IR Cut Removable)
 0 Lux (IR On) Min. Illumination
 ONVIF

Digital WDR
 3D Noise Reduction
 Motion Detection and Privacy Masking
 3-11mm Vari-Focal Lens
 25m IR Illumination

PoE Support
 IP 66 Protection

Specifications

Camera	Video	Model	DI-330IPSVF
		Image Sensor	1/3" CMOS
		Effective Pixels	2048x1536
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30FPS
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	No
		Communication	No
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
Image Enhancement		Digital WDR, ROI	
Noise Reduction		3D-DNR	
Image Orientation		Mirror/Flip	
Privacy Zone		Yes	
Motion Detection		Yes	
Compression	Video Compression	H.264 / MJPEG (Sub-Stream Only)	
	Resolution	3MP (2048x1536), 1080P (1920x1080), 720P (1280x720), D1, CIF	
	Multi-stream	2048x1536 (1~30fps) / 1920x1080 (1~30fps) / 1280x720 (1~30fps) D1 (1~30fps) / HD1 (480x240) CIF (1~30fps)	
	Bit rate	64Kbps ~ 10Mbps	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	25m (2 High Power IR LED)
	Lens	3-11mm Vari-Focal
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis Wall Bracket
	Dimensions	Ø120mm×100mm
	Weight(gross)	400g
Connectivity	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	No
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
	ONVIF	Yes
Others	Ethernet	100Mbps
	PoE	Yes
Power Supply	Power Supply	DC12V/-280mA / PoE/-4W
	Work Environment	-30 C~50 C, 10%~90% Humidity

