


IR FIXED LENS DOME CAMERA

DI-340IP528
DI-340IP536



1/3" CMOS Sensor
4 Mega-Pixel
True Day & Night (IR Cut Removable)
H.265 (HEVC) Compression
0 Lux (IR On) Min. Illumination

ONVIF
True WDR / BLC / HLC
3D Noise Reduction
Motion Detection and Privacy Masking
2.8mm/3.6mm Mega-Pixel Lens

15m IR Illumination
PoE Support
1 Way Audio
CVBS
IP 66 Protection

Specifications

Camera	Model	
	DI-340IP528	DI-340IP536
Video	Image Sensor	1/3" CMOS
	Effective Pixels	2688x1520
	Electronic Shutter	1/25s ~ 1/100000s
	Frame Rate	Standard: 1-25/30 (True-WDR), HFR*: 1-50/60 (Max. 1080P & D-WDR)
	Day & Night	ICR
	Min. Illumination	0lux (IR ON)
	Audio	Audio compression
Communication		One-way Audio
Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto)
	Image Enhancement	Sharpness, Saturation, Brightness & Contrast Adjustable
	Noise Reduction	3D-DNR
	Image Orientation	Mirror/Flip
	Privacy Zone	Yes
	Motion Detection	Yes
	Compression	Video Compression
Resolution		4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240
Multi-stream		4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS / 1~50/60FPS with HFR*)
Bit rate		64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264
Encode Mode		VBR/CBR
Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	15m (2 High Power IR LED)	
	Lens	2.8mm (DI-340IP528)	3.6mm (DI-340IP536)
	Iris	Fixed Iris	
	Lens Mount	Φ14 mount	
	Water-proof	IP66	
	Bracket	3-Axis Wall Bracket	
	Dimensions	Ø107mm×95mm	
Connectivity	Weight(gross)	400g	
	Network	RJ45 (+PoE)	
	Power	DC Socket	
	Analog Video Output	CVBS (RCAX1)	
	Mic Connectivity	1Ch Input	
	SD Card	No	
	RS485	No	
Network	Alarm	No	
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App	
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission	
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP	
	ONVIF	Yes	
	Ethernet	100Mbps	
	PoE	Yes	
Others	Power Supply	DC12V/-280mA / PoE/-4W	
	Work Environment	-30 C ~50 C , 10%~90% Humidity	

*HFR (High Frame Rate) must be supported by the NVR in order to work properly.

