

IR FIXED LENS VANDAL-PROOF MINI DOME CAMERA

DMA-340IP536



1/3" CMOS Sensor
 4 Mega-Pixel
 True Day & Night (IR Cut Removable)
 H.265 (HEVC) Compression
 0 Lux (IR On) Min. Illumination
 ONVIF

True WDR / BLC / HLC
 3D Noise Reduction
 Motion Detection and Privacy Masking
 3.6mm Mega-Pixel Lens
 10m IR Illumination
 PoE Support

Local Storage
 1 Way Audio
 Built-In Microphone
 CVBS
 IP 66 Protection
 IK 10 Vandal Proof

Specifications

Camera	Video	Model	DMA-340IP536
		Image Sensor	1/3" CMOS
		Effective Pixels	2688x1520
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	Standard: 1-25/30 (With True-WDR), HFR: 1-50/60 (Without True-WDR)
		Day & Night	ICR
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto)
		Image Enhancement	Sharpness, Saturation, Brightness & Contrast Adjustable
Noise Reduction		3D-DNR	
Image Orientation		Mirror/Flip	
Privacy Zone		Yes	
Compression	Motion Detection	Yes	
	Video Compression	H.265 / H.264	
	Resolution	4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240	
	Multi-stream	4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS / 1~50/60FPS with HFR*)	
	Bit rate	64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	10m (12 IR LED)
	Lens	3.6mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66 / Vandal Proof: IK10
	Bracket	3-Axis Gimbal
	Dimensions	Φ110mm×57.8mm
	Weight(gross)	350g
	Network	RJ45 (+PoE)
	Power	DC Socket
Connectivity	Analog Video Output	CVBS (BNCx1)
	Mic Connectivity	Built-In Microphone + Mic Input
	SD Card	Support recording over TF (128GB Max)
	RS485	No
	Alarm	No
Network	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
	ONVIF	Yes
	Ethernet	100Mbps
Others	PoE	Yes
	Power Supply	DC12V/~340mA / PoE/~4.7W
	Work Environment	-30 C ~ 50 C, 10%~90% Humidity

*HFR (High Frame Rate) must be supported by the NVR in order to work properly.

